



SILO AND AUGER CONVEYING SYSTEM

料塔及绞龙输送系统



绞龙输送系统特点：

- ⊕ 采用进口绞龙，性能稳定，使用寿命长。
- ⊕ 适用于粉料、颗粒料和片状饲料输送，无质量损失，无积料。
- ⊕ 安装简单，方便，快捷。

Advantages of auger conveying system:

- ⊕ Using imported auger to achieve a stable performance and long service life.
- ⊕ Applying for different types of feed, like powdery, grainy and lamellate type, to achieve the goals with no waste and no accumulation.
- ⊕ Easy for installation, convenience and quick to use.

型号 Model No.	LJ60	LJ75	LJ90	LJ125
水平输送能力 (kg/h) horizontal transportation ability	600	1400	2500	6000
输送距离(m) conveying distance	100	75	40	18
驱动功率(kW) driving power	0.75	0.75	0.75/1.1	1.5
料管直径(mm) diameter of feed pipe	60	75	90	125
料管材质 material of feed pipe	PVC	PVC	PVC	PVC
料管壁厚(mm) thickness of feed pipe	4	3.7	4.2	4.8
螺旋外径(mm) OD of auger	45	60	70	95
螺旋节距(mm) pitch of auger	45	60	56	66